

Sewn open sling for creating the anchor point.

DESCRIPTION

Different color according to length.

Suitable for anchoring and connecting when working at heights.

Width 20 mm.

KEY FEATURES

width 20 mmmade of PES

STANDARDS

C € 1019

EN 795B EN 354 EN 566



FEATURES







20 mm



60/80/ 120/150 cm



l person only



55/70/ 105/130 g



unique number



warranty

MATERIALS

TECHNICAL DATA





CODE	COLOR	LENGTH	WEIGHT
W2001Y060	yellow	60 cm / 24 in	55 g /1.9 oz
W2001A080	blue	80 cm / 32 in	70 g / 2.5 oz
W2001R120	red	120 cm / 48 in	105 g / 3.7 oz
W2001B150	black	150 cm / 60 in	130 g / 4.6 oz
W2001B060	black	60 cm / 24 in	55 g /1.9 oz
W2001B080	black	80 cm / 32 in	70 g / 2.5 oz
W2001B120	black	120 cm / 48 in	105 g / 3.7 oz



W2001 Version: 06/2024

MAINTENANCE

Lifetime of this product depends on the frequency and the environment (salt, sand, moisture, chemicals, etc.) in which is used. Without taking wear or mechanical damage into account and in compliance with the conditions specified in the instructions for use this product may be used 15 years from the date of production and 10 years from the date of the first use.

However mechanical damage can occur during the first use, which can limit the lifetime of this products only to its first use.











drying



beware of salt


beware of UV

beware of chemicals

washing

read instructions

OTHER VIEWS



Available also in black only (anthracite stitching).

